



Ž Two-Roller construction for cold water-based adhesives

Ž Machine will cut coating costs to 50 %. The labor-saving alone pays for the machine many times over

Ž Two-Roller constructions permits adjustable and precise coating over the entire sheet

Action : The sheets will be feeded between the infeed rollers to the glue application roller. Stripper Fingers picking up the sheets from the roller.

Options : Card-Board-Attachment for rigid/thick materials as corrugated board stock, chipboard, etc up to 25 mms. Strip- and Edge Gluing Attachment

Cleaning : Easy cleaning without loosing screws or using tools.

Motor : Motor for 230 volts AC 50 cy 1 ph, other currents/voltages on request. Variable speed control.

Working size	Weights / kg		Dimensions	
	net	gross	machine	case
200 mm	40	50	40 x 45 cm	50 x 48 x 30 cm
250 mm	43	53	50 x 45 cm	60 x 48 x 30 cm
350 mm	50	60	60 x 45 cm	70 x 50 x 30 cm

SUMBEL GMBH

D-28197 Bremen - Carl-Stockhinger-Str. 5 - Germany

Telf. ++49 (421) 544078 - Fax ++49 (421) 544071

Homepage: <http://www.sumbel.de> - E-Mail: sumbel@t-online.de